



Neogi Technologies & Research Pvt Ltd

2, Kumarpara Road, P.O –Rajpur, Kolkata -700149, West Bengal, India

PHONE NUMBER: +91.33.24778866 / 4335 / 9320

MOBILE NUMBER: +919830705545, EMAIL: sales@ntrindia.co.in

PRODUCT SPECIFICATION

MECHANICAL MOBILE FUEL DISPENSING UNIT LEGAL METROLOGY APPROVED 5 DIGIT

- **NAME OF THE PRODUCT :** Meter For Volumetric Measurement (5Digit)
- **MODEL NO:** NTR/06
- **AVAILABLE MODELS :** MECHANICAL
- **DIMENSIONS :** 24.1cm x 26cm x 42cm
- **WEIGHT :** 15 KG(APPROX)
- **ACCURACY :** +/- 0.1%
- **FLOW RATE :** UPTO 90 LPM
- **TYPE :** Positive Displacement Meter
- **BODY MATERIAL :** CRCA SHEET
- **REPEATABILITY :** 100%
- **DISPLAY :** MECHANICAL(4 DIGIT/5 DIGIT)
- **PRINTER :** NO
- **TOTALIZER :** MECHANICAL (99,99,999.9)
- **CERTIFICATION :** LEGAL METROLOGY GOV. OF INDIA, INDIA DESIGN MARK
- **NOZZLE :** MANUAL & AUTOSHUTOFF (AS PER CUSTOMER NEED)
- **HOSE PIPE :** 4MTR, 6 MTR, 8 MTR (AS PER CUSTOMER REQUIREMENT)
- **LINE FILTER :** 1 INCH, 1.5 INCH

BATTERY OPERATED (BLDC) PUMP UNIT

- **NAME OF THE PRODUCT :** BATTERY OPERATED (BLDC) PUMP UNIT
- **MODEL NO:** SP/040
- **AVAILABLE MODELS :** WITH 12 VOLT MOTOR / 24 VOLT MOTOR
- **DIMENSIONS :** 280MM X 150MM X 190 MM
- **WEIGHT :** 6.9KG(APPROX)
- **ACCURACY :** N/A

- FLOW RATE : UPTO 40 LPM
- TYPE : Positive VANE TYPE PUMP
- BODY MATERIAL : CI
- REPEATABILITY : N/A
- DISPLAY : N/A
- PRINTER : N/A
- TOTALIZER : N/A
- CERTIFICATION : N/A
- SUCTION LIFT : UPTO 1.7m (Manual Nozzle) UPTO 1.5m (Automatic Nozzle)
- OPERATING TEMPERATURE : -5° C TO +120°C
- END CONNECTION : Inlet- 25.4mm/19.5mm , Outlet :25.4/19.05mm
- INBUILT STRAINER: YES

PTO PUMP UNIT

- NAME OF THE PRODUCT : PTO PUMP UNIT
- MODEL NO: SP/080
- AVAILABLE MODELS : ROTARY GEAR PUMP UNIT
- DIMENSIONS : 350 MM X 270 MM X 250 MM
- WEIGHT : 16.8 KG
- ACCURACY :N/A
- FLOW RATE : UPTO 80 LPM
- TYPE : ROTARY GEAR PUMP UNIT
- BODY MATERIAL : CI
- REPEATABILITY : N/A
- DISPLAY : N/A
- PRINTER : N/A
- TOTALIZER : N/A
- CERTIFICATION : N/A
- SUCTION LIFT : 3 METERS
- OPERATING TEMPERATURE : -5° C TO +120°C
- END CONNECTION : Inlet- 38mm , Outlet : 25.4mm
- INBUILT STRAINER: YES